

remote display V60N-AS



area of application

Very compactly and lightweight remote-display. Easy readable up to 30 meters. Applicable for indoor and outdoor including direct sunlight. Accepts serial strings from PC, PLC or indicator (Systec, Mettler, Schenck, Rhewa, Rinstrum, Sartorius, DS, Every GSE, Soehnle, Pfister, Vishay, Dini Argeo etc.)

technical specification

power supply:	110 - 240 VAC
enclosure:	aluminium, wall thickness 3 mm (0.118 inches)
protection class:	IP65
dimension:	420 x 100 x 50 mm (16.54x3.93x1.97 inches) (WxHxD)
weight:	1.6 kg (3.5 lb)
character:	6 characters + traffic light, hight 60 mm (2.36")
viewing range:	up to 30 meters (100 ft)
reading angle:	140° all around
brightness:	sun readable, 16 position or automatically adjust (sensor)
operating environment:	-20°C bis +60°C (-4°F to 140°F), with temperatur control
input data interface:	RS232, RS485 optional: wireless RF, ethernet
status led's:	red or green
data protocol:A1	<STX>Data<ETX> <STX>AddressData<ETX> Data<CR><LF> Data<CR> <STX>Data<EOT> <STX>Data<CR> incl. special funktion traffic light and status information

options

wireless RF, ethernet
units: kg / t / g / lb / and other

www.vtec.ch/VxxxDGA.htm

manuals, drawings, pc-software, firmware, pictures