

remote display V10C



V10C



V10C-AS

area of application

Very compactly and lightweight remote-display.

Easy readable up to 4 meters.

Accepts serial strings from PC, PLC or indicator (Systec, Mettler, Schenck, Rhewa, Rinstrum, Sartorius, DS, Every GSE, Soehnle, Pfister, Vishay, Dini Argeo etc.)

technical specification

power supply:	9 - 36 VDC
enclosure:	Polycarbonat
protection class:	IP 50
dimension:	160 x 80 x 60 mm (LxHxT)
weight:	0.280 kg
character:	6 characters, hight 10 mm
viewing range:	up to 12 meters (13 ft)
reading angle:	120° all around
brightness:	16 position
operating environment:	-20°C bis +60°C (-4°F to 140°F), with temperatur control
input data interface:	RS232, RS485 optional: wireless RF
data protocol:	<STX>Daten<ETX> <STX>AdresseDaten<ETX> Daten<CR><LF> Daten<CR> <STX>Daten<EOT> <STX>Daten<CR> incl. special funktion

options

wireless RF, ethernet

units: kg / t / g / lb / and other
within status LED's (V10C-AS)

www.vtec.ch/VxxxDGA.htm

manuals, drawings, pc-software, firmware, pictures